




TECHNICAL SHEET FA 60 002 00

Tripod for access in confined spaces – Maximum height 2,90 m



	A	B	∅
Mini	129 cm	111 cm	150 cm
Maxi	168 cm	134 cm	180 cm



- With two mounted pulleys at the head of the Tripod in the extension of the main leg for passing a cable.
- Having two auxiliary eye bolts as attachment points.
- Aluminum alloy cast head, legs in aluminum.
- Steel support-shoes provided with rubber sole to increase friction and impart more stability
- **Strength of anchorage** point greater than > 12kN.
- Every Tripod is provided with inbuilt fixture for attaching our winch FA 60 003 00 (20 m) or FA 60 023 00 (30 m).
- Every Tripod is provided with Tripod Bag.
- **Compliance** : Conforms to EN 795:2012 Type B.

Maximum load capacity : 500 kg.

Matériel de composants :

Legs : Aluminium
 Head : Aluminium alloy cast
 Inbuilt fixture, support-shoes : Steel

Max height:	CE	Weight :
2,90 m		15 kg

KRATOS SAFETY

ZI les Portes du Dauphiné
 4, rue de l'Aigue
 69780 Saint Pierre de Chandieu – FRANCE

Tel : +33 (0)4 72 48 78 27

Fax : +33 (0)4 72 48 58 32

www.kratossafety.com / info@kratossafety.com

HS CODE

76109010

CARTON SIZE / PIECES

210x30x28 / 1

AET N° 2129 Issue 3 Extension 3

Satra Technology Centre, N°0321
 Wyndham Way, Telford Way, Kettering
 Northamptonshire, NN16 8SD, United Kingdom

ARTICLE 11 GB07/73551

SGS United Kingdom Ltd., N°0120
 Unit 202B, Worle Parkway,
 Weston-super-Mare, BS22 6WA, United Kingdom